# HyFlex® 11-318

## **MECHANICAL PROTECTION**



STYLE #	CONSTRUC- TION	GAUGE	LINER Material	COATING Material	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-318	Knitted	18	Dyneema® Diamond, Spandex, Nylon and Carbon	N/A	Uncoated	Knitwrist	Grey	6, 7, 8, 9, 10, 11	208 - 254	12 pairs in a bag, 12 bags in a carton



#### **DESCRIPTION**

- The HyFlex® 11-318 brings a new degree of dexterity to applications with cut risks: it is the first uncoated glove to provide EN Level 3 cut protection in an 18 gauge liner.
- Its ultra light fabric creates a sensation of bare hand contact and helps to maintain the hand at a comfortable working temperature. It offers a snug/ergonomic fit on the hand thanks to the spandex
- reinforcement in the tension areas of the hand (knuckles and palm).
- This low lint glove is also silicone free and anti-static to ensure worker and product protection. Furthermore a specific packaging was developed in order to prevent silicone contamination from plastic bags.

## REMARKS

- Antistatic according to EN1149
- Electrostatic discharge protection

## FEATURED TECHNOLOGY

Dyneema® Diamond Technology

## Best-in-class protection and performance with unmatched comfort

PRIMARY INDUSTRIES







## **IDEAL APPLICATIONS**


- Final assembly of sharp parts
- Packaging
- Quality inspection before painting



**CATEGORY II** 



Print date: 08-04-2017



Riverside Business Park, Block J Boulevard International 55, 1070 Brussels, Belgium Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03 http://www.ansell.eu • E-mail info@ansell.eu

