



Suitable industries	
Abrasion	0 ————— ● ————— 8000 cycles
Cut	ISO 13997: C (A-F) ANSI: not tested (A1-A9)
Tear	0 ————— ● ————— 75 N
Puncture	0 ————— ● ————— 150 N
Impact	 ✗
Needle	 25 gg: ✗
Heat	 ✗
Water & Oil	 ✗
Grip	Dry: ————— ● ————— Wet/Oil: ————— ● —————
Breathing	Low ————— ● ————— High



A: ABRASION (1-4)
B: CUT (1-5)
C: TEAR (1-4)
D: PUNCTURE (1-4)
F: ISO CUT (A-F)
P: IMPACT PROTECTION

ISO CUT (A-F)
A | ≥ 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | ≥ 22 N
F | ≥ 30 N



Glove Purpose	Ultra thin cut resistant glove for dry/wet applications
Name & Number	18-3 Cool SupraCoat - 18-3CSC
Materials	HPPE, Fibreglass, Elastane, PU composite
Colour & Thickness	 Palm: 0,8 mm Back of hand: 0,5 mm
Size & Packing	 6 pairs / plastic bag 60 pairs / carton